




Versati IV

SPLIT TYPE



- Versati Split izvedba se sastoji od vanjske jedinice i unutarnje jedinice (hidroboxa)
- Omogućuje grijanje i hlađenje prostora te pripremu potrošne tople vode do 65 °C
- LCD zaslon visoke rezolucije na dodir s podrškom za 20 jezika
- Mogućnost Wi Fi upravljanja
- Sustav koristi rashladni medij R32, a jedinice su certificirane Eurovent certifikatom

MODEL	UČINAK (W)		EER A35/W7 A35/W18	COP A7/W35 A7/W45
	HLADNJE A35/W7 A35/W18	GRIJANJE A7/W35 A7/W45		
Napajanje: 1Ph / 220-240 V / 50 Hz				
GRS-CQ4.0Pd/NhH3-E (O)	4 200 / 4 500	4 300 / 4 200	3,55 / 5,6	5,45 / 4,00
GRS-CQ4.0Pd/NhH3-E (I)				
GRS-CQ6.0Pd/NhH3-E (O)	6 200 / 6 500	6 200 / 6 000	3,35 / 5,4	5,25 / 4,00
GRS-CQ6.0Pd/NhH3-E (I)				
GRS-CQ8.0Pd/NhH3-E (O)	7 300 / 8 400	8 300 / 8 200	3,40 / 5,20	5,30 / 3,95
GRS-CQ8.0Pd/NhH3-E (I)				
GRS-CQ10Pd/NhH3-E (O)	8 700 / 10 200	10 200 / 10 000	3,2 / 4,95	5,0 / 3,9
GRS-CQ10Pd/NhH3-E (I)				
GRS-CQ12Pd/NhH3-E (O)	11 100 / 12 200	11 700 / 12 500	2,9 / 3,89	4,91 / 3,84
GRS-CQ12Pd/NhH3-E (I)				
GRS-CQ14Pd/NhH3-E (O)	11 900 / 13 500	14 200 / 13 900	2,77 / 3,57	4,77 / 3,74
GRS-CQ14Pd/NhH3-E (I)				
GRS-CQ16Pd/NhH3-E1 (O)	13 500 / 14 900	16 000 / 16 000	2,65 / 3,7	4,55 / 3,65
GRS-CQ16Pd/NhH3-E (I)				
Napajanje: 3Ph / 380 - 415 V / 50 Hz				
GRS-CQ16Pd/NhH3-M1 (O)	13 500 / 14 900	16 000 / 16 000	2,65 / 3,6	4,6 / 3,7
GRS-CQ16Pd/NhH3-M (I)				

